

Visor Electrónico **Vix Txiki**

CARACTERISTICAS TÉCNICAS

Mando control remoto con visor de LCD 10mm.
Receptor vía radio multicanal.
Aplicable a todos los modelos de pesajeinalámbricos DINAKSA.
No necesita instalación.
Visualización de peso con una sola pulsación.
Funciones TARA y suma acumulativa.
Funciones de calibración del equipo de pesaje.
Alcance máximo 150 metros, en función de las condiciones.
Alimentación: Pila de 9Vcc. 6LR61.
Temperatura de funcionamiento -10°C a +55°C.Humedad 15%-85%
Dimensiones 60X102X27mm.
Autonomía 100 horas a 20°C.
Frecuencia de trabajo UHF 870 Mhz (6 canales).
Potencia de transmisión 10mW.
Visualización / repetidor de varios equipos a la vez.



Electronic Display **Vix Txiki**

TECHNICAL FEATURES

Remote control display with 10 mm. LCD digits.
Multichannel via radio receiver.
Suitable for all the DINAKSA wireless weighing devices.
It doesn't need installation.
Weight display using a single key-press.
TARA and accumulative adding functions.
Weighing equipment calibration functions.
Maximum range: 150 mts, depending on conditions.
Power supply: 9 Vcc. 6LR61 battery.
Working temperature: -10°C to +55°C
Humidity: 15% to 85%.
Dimensions: 60x102x27 mm.
Working autonomy: 100 hours at 20°C.
Working frequency: UHG 870 Mhz (6 channels).
Power transmission: 10 mW
Available to work with 8 weighing devices.

