

Características Técnicas.

Capacidades desde 1.000 hasta 31.500kg.

Display LED números rojos con 5 dígitos de 75 mm.

Carcasa de acero pintado epoxi

Precisión: $\pm 0,03\%$ sobre capacidad máxima

Temperatura de trabajo: desde -20 a 70°C

IP 50

Memoria sumadora activa por teclado frontal y mando IR

Mando infrarrojo para las funciones OFF, TARA, memoria sumadora, totalizador y borrados

Apantallamiento contra interferencias

Se suministra con cargador automático y batería de larga duración recargable

Suministro completo de accesorios (anilla, 2 grilletes, gancho giratorio con pestillo de seguridad, cargador de batería)

Máxima robustez con mínimo peso

Mínima altura perdida en grúa

Sobrecarga puntual del 150% sin dañar la célula

Autonomía de funcionamiento aprox. 40h.


Consumo reducido (Low power)

Cambio rápido de pack de batería sin herramientas (Quick drop)

Alta estabilidad en peso y rápida respuesta de lectura

Fabricación nacional con control metrológico acreditado nº 01M042

CAPACIDAD (Kg)	RESOLUCIÓN (Kg)	DIMENSIONES				PESO (Kg)
		A	B	C	D	
1000	0,2	500	235	335	400	7
2000	0,5	500	235	335	400	7
3150	0,5	570	260	400	430	8
5000	1	700	265	370	595	13
6300	1	770	330	500	600	16
9500	2	840	335	465	710	24
12000	5	900	350	540	710	27
15000	5	1050	360	635	775	44
22000	10	1300	580	890	990	71
25000	10	1375	580	890	1065	79
30000	20	1450	660	980	1130	106
31500	20	1450	660	980	1130	106



Wi-Fi

Bluetooth

Opciones

Mando vía radio para las funciones OFF, TARA, memoria sumadora, totalizador y borrados.

Impresora integrada

Preselección de carga

Servicio 24h: 2 juegos de baterías intercambiables Plug & Play y base de carga Dock Station

Protección anti-calórica BASIC para fundiciones

Protección anti-calórica PLUS para fundiciones

Protección anti-choque

Otras IP consultar

Pico máximo

Emisor Wifi



Emisor Bluetooth



Emisor radio para equipos DK Dinaksa

Auto apagado programable (a petición)

Certificado de calibración (a petición)

Carcasa de acero inoxidable (acabado satinado)

Consúltenos sus necesidades específicas

Protección
anticalórica PLUS

Quick drop

Opción impresora
integrada.



Crane Scale **Excel75**

TECHNICAL FEATURES

Capacity from **1.000 kg up to 31.500 kg.**

Red LED Display with 5 digits 75 mm high.

Epoxy painted steel housing

Accuracy: $\pm 0,03\%$ on the maximum capacity.

Working temperature: -20°C to 70°C .

IP 50

Adding memory active through front keyboard and IR remote control.

Infrared remote control for the OFF, TARE, adding memory, totalizer and delete functions.

Screening against interference.

Supplied with a long-life rechargeable battery and automatic charger.

Includes all the accessories: Ring, 2 shackles, swivel hook with safety latch and battery charger.

Maximum strength with minimum weight.

Minimum height loss in crane.

150% overload without damaging the cell.

40h approx. working autonomy.


Low power consumption.

Quick battery change pack without tools (Quick drop)

High stability on weight and fast response reading.

National manufacturing with accredited metrological control nº 01M042

Capacity (Kg)	Resolution (Kg)	Dimensions				Weight (Kg)
		A	B	C	D	
1000	0,2	500	235	335	400	6,7
2000	0,5	500	235	335	400	6,7
3150	0,5	570	260	400	430	8,6
5000	1	700	265	370	595	13,03
6300	1	770	330	500	600	16,4
9500	2	840	335	465	710	24,7
12000	5	900	350	540	710	27,56
15000	5	1050	360	635	775	44,87
22000	10	1300	580	890	990	71,8
25000	10	1375	580	890	1065	79,56
30000	20	1450	660	980	1130	106
31500	20	1450	660	980	1130	106



OPTIONS



Infrared remote control for the OFF, TARE, adding memory, totalizer and delete functions.

Via radio remote control for the OFF, TARE, adding memory totalizer and delete functions.

Integrated printer.



Load preselection (includes a remote control).

24h service: 2 sets of Plug & Play batteries and Dock Station

BASIC protection against heat hazards for castings.

PLUS protection against heat hazards for castings.

Protection against impact.

Other IP protection levels, on request.

Maximum peak indicator.

WiFi, Bluetooth or Radio transmitter for DINAKSA equipments.

Programmable auto power off (on request).

Calibration certificate (on request).

Stainless steel housing.


Contact us for your specific needs.



**PLUS
Protection**



Quick- Drop



**Integrated
Printer**

