

Dinamómetro Electrónico **Macro**

Características Técnicas

Capacidades desde 30.000 hasta 100.000 kg

Display LED números rojos con 5 dígitos de 20 mm a 75 mm

Carcasa de acero pintado epoxi

Precisión: 0.03%

Temperatura de trabajo: desde -20 a 70 °C

IP 50

Memoria sumadora activa por teclado frontal y mando IR

Mando visualizador **TXIKI** para las funciones OFF, TARA, memoria sumadora, totalizador y borrados

Apantallamiento contra interferencias

Se suministra con cargador automático y batería de larga duración recargable

Suministro con 2 grilletes y cargador de batería

Máxima robustez con mínimo peso

Mínima altura perdida en grúa

Sobrecarga puntual del 150% sin dañar la célula

Autonomía de funcionamiento aprox. 40 h

Consumo reducido (Low Power).

Cambio rápido de pack de batería sin herramientas (Quick Drop)

Alta estabilidad en peso y rápida respuesta de lectura.



Fabricación nacional con control metrológico acreditado nº 01M042

Capacidad (Kg)	Resolución (Kg)	Dimensiones (mm.)	Peso (con grilletes) (Kg)	Peso (sin grilletes) (Kg)
		A		
35.000	20	660	64	
50.000	20	950	136	
75.000	50	950	136	
10.000	50	1090	295	
>100.000	BAJO PROYECTO			

Opciones

Transmisión de datos vía radio, WIFI o Bluetooth para equipos DK Dinaksa o PC

Servicio 24h: 2 juegos de baterías intercambiables Plug & Play y base de carga

Dock Station

Preselección de carga

Protección anti-calórica Plus para fundiciones

Pico máximo

Emisor Wifi



Emisor Bluetooth



Emisor radio para equipos DK Dinaksa

Auto apagado programable (a petición)

Certificado de calibración (a petición)

Otras IP, consultar

Consúltenos sus necesidades específicas.



Crane Scale **Macro**

TECHNICAL FEATURES

Capacity from **30.000 kg up to 100.000 kg.**

Red LED Display with 5 digits 75 mm high.

Epoxy painted steel housing

Accuracy: 0.03%

Working temperature: -20 to 70°C

IP 50

Adding memory active through front keyboard and IR remote control.

Infrared remote control for the OFF, TARE, adding memory, totalizer and delete functions.



Screening against interference.

Supplied with a long-life rechargeable battery and automatic charger.

Supplied with 2 shackles and battery charger.

Maximum strength with minimum weight.

Minimum height loss in crane.

150% overload without damaging the cell.

Working autonomy: 40h approx.

Low power consumption.

Quick battery change pack without tools (Quick drop).

High stability on weight and fast response reading.



National manufacturing with accredited metrological control No. 01M042

Capacidad (Kg)	Resolución (Kg)	Dimensiones (mm.)	Peso (con grilletes) (Kg)	Peso (sin grilletes) (Kg)
		A		
35.000	20	660	64	
50.000	20	950	136	
75.000	50	950	136	
10.000	50	1090	295	
>100.000	BAJO PROYECTO			

OPTIONS

24h service: 2 sets of Plug & Play batteries and Dock Station charging dock.

Load preselection

PLUS protection against heat hazards for castings.

Other IP protection levels, on request

Maximum peak indicator.

WiFi transmitter.

Bluetooth transmitter.

Radio transmitter for DINAKSA equipments.

Programmable auto off (on request).

Calibration certificate (on request).

Contact us for your specific needs.

